

Ultra Stripper GEL



Rinseless Mop Strip

Estripádo Sin Enjuague

- Instant Emulsification • Penetrating
- Time Saver • Works With Cold Water

Simple Stone Care



Technical Data Sheet

PRODUCT DESCRIPTION:

A non-corrosive, rinseless, mop-on stripper formulated to immediately rip off multiple layers of finish or sealer using cold or warm water.

USES:

Strips off multiple coats of wax and finish without the use of a floor machine and stripping pad.

ADVANTAGES:

Cuts through many layers of sealer and finish in minutes. No rinse is necessary when the residue is picked up with a wet vacuum. A tremendous time and labor saver. Non-corrosive.

SPECIFICATIONS:

Active Ingredients: 70%
 pH: 12
 Color: Blue
 Solubility in Water: Complete
 Odor: Lemon
 Flash Point: None
 Viscosity: Water Thin
 Weight per Gallon: 8.1 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Unit, 5 Gallon Pail,
 30 & 55 Gallon Drums.
 1 Quart Unit, 12 to a case



Recyclable packaging

PRODUCT USE

PRODUCT USE	DILUTION RATE
Light Build-Up	8 oz. per gallon of cold or warm water
Medium Build-Up	32 oz. per gallon of cold or warm water
Heavy Build-Up	64 oz. per gallon of cold or warm water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE
 PRODUCT DESIGNED FOR USE WITH WARM WATER

DIRECTIONS FOR PRODUCT USE:

FOR BEST RESULTS, USE OF WET-VAC IS RECOMMENDED

1. Dilute concentrate per the chart above based on the amount of build-up.
2. Apply to a small test area to determine the amount of time needed to adequately strip floor.
3. Mop diluted solution liberally onto floor surface working in 5' x 5' sections or use autoscrubber for application.
4. Allow to stand 4-5 minutes. Keep area wet.
5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
7. Allow floor to dry.
8. Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

CAUTION: Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to MSDS for further safety information.



MANUFACTURED BY:

Simple Stone Care

Ph: 516-719-0510 Fax: 516-719-0511

www.simplestonecare.com

