



Rust Eater GEL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/15/2015

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Rust Eater
Product code : CARE.SSC.RUSTREMSEL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Floor cleaning (liquids)

1.3. Details of the supplier of the safety data sheet

Simple Stone Care, Inc.
P.O. Box 1384
Bayville, NY 11709
PH: 516-719-0510 Fax: 516-719-0511

1.4. Emergency telephone number

Emergency number : (800) 535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) Category 4 H302

Skin corrosion/irritation Category 1A H314

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS05

GHS07

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US)

: P260 - Do not breathe dust/mist/spray
P264 - Wash hands and forearms thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves/eye protection/face protection
P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor
P321 - Specific treatment (see First aid measures on this label)
P330 - Rinse mouth
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Ammonium hydrogen difluoride	(CAS No) 1341-49-7	10 - 20	Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314
Oxalic acid, dihydrate	(CAS No) 6153-56-6	5 - 10	Skin Corr. 1A, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity	: Thermal decomposition generates : corrosive vapors.
------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Oxalic acid, dihydrate (6153-56-6)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (Oxalic acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (mg/m ³)	2 mg/m ³ (Oxalic acid; USA; Short time value; TLV - Adopted Value)
Ammonium hydrogen difluoride (1341-49-7)		
Not applicable		

8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves/eye protection/face protection protective gloves.
- Eye protection : Chemical goggles or face shield.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Colorless
- Odor : characteristic
- Odor threshold : No data available
- pH : 3
- Melting point : No data available
- Freezing point : No data available
- Boiling point : 212 - 220 °F
- Flash point : 200 °F
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : 1.15
- Relative vapor density at 20 °C : Same as water

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : • : 14 g/100ml • : 63 g/100ml
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Rust Eater	
ATE US (oral)	925.267 mg/kg body weight
Ammonium hydrogen difluoride (1341-49-7)	
LD50 oral rat	130 mg/kg (Rat; Literature)
ATE US (oral)	130.000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 3
Serious eye damage/irritation	: Not classified pH: 3
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



SECTION 12: Ecological information

12.1. Toxicity

Oxalic acid, dihydrate (6153-56-6)	
LC50 fish 1	34.1 mg/l (LC50; 96 h)
EC50 Daphnia 1	137 mg/l (EC50; 48 h)
Ammonium hydrogen difluoride (1341-49-7)	
LC50 fish 1	562 mg/l (96 h; Brachydanio rerio)
LC50 fish 2	237 mg/l (96 h; Brachydanio rerio)

12.2. Persistence and degradability

Rust Eater	
Persistence and degradability	Not established.
Oxalic acid, dihydrate (6153-56-6)	
Persistence and degradability	Readily biodegradable in water. Readily biodegradable in water in anaerobic conditions. Photolysis in water. Biodegradable in the soil. Photolysis in the air.
Ammonium hydrogen difluoride (1341-49-7)	
Persistence and degradability	Biodegradability: not applicable.
ThOD	Not applicable

12.3. Bioaccumulative potential

Rust Eater	
Bioaccumulative potential	Not established.
Oxalic acid, dihydrate (6153-56-6)	
Log Pow	-1.74 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Ammonium hydrogen difluoride (1341-49-7)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1760 Compounds, cleaning liquid (Contains Ammonium Bifluoride), 8, II

UN-No.(DOT) : NA1760

Proper Shipping Name (DOT) : Compounds, cleaning liquid
Contains Ammonium Bifluoride

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized
N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table
T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: t_r is the maximum mean bulk temperature during transport, t_f is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (t_f) and the maximum mean bulk temperature during transportation (t_r) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d_{15} and d_{50} are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Oxalic acid, dihydrate (6153-56-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Rust Eater

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Ammonium hydrogen difluoride (1341-49-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 100 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 04/15/2015

Other information : None.

Full text of H-phrases:

H301	Toxic if swallowed
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal Protection : E

E - Safety glasses, Gloves, Dust respirator

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.